# FRAMMENTO SHWR PK2

### FRAMMENTO Shower Range Frammento Shower Pack 2 Complete



Specification					
Finish/Colour:	Chrome Plated				
Main Construction Material:	Brass; ABS				
No of Controls:	2				
Shower Type:	Dual Control				
Shower Head Type:	Both				
Shower Kit:	Fixed Head				
Valve/Cartridge Type:	3/4" Ceramic Disc Valve 1/4 turn				
Maximum Hot Water Supply Temperature °C:	65				
Plumbing System Suitability:	Suitable for all plumbing systems				
Minimum Dynamic Pressure (bar):	0.2				
Maximum Dynamic Pressure (bar):	5				
Maximum Static Pressure (bar):	10				
Connection Inlet:	15mm Compression				
Connection Outlet:	G 1/2"				
Isolation Valve Included:	No				
Check Valve Included:	Yes				

Dimensions (measurements in mm)

#### Features:

- All in one box pack includes shower valve with integral two outlet diverter, slimline 250mm round fixed head with shower arm, and shower hose with integral handset holder and wall outlet plus a single function handset and wall outlet.
- Rub clean handset and fixed head

   limescale and debris build-up
   is quickly and easily removed by
   rubbing a finger or a cloth over
   the nozzles.
- A hard-wearing, flawless, scratch resistant chrome finish that lasts for years. Salt spray tested to ensure added durability.
- Slim design recessed shower valve will fit into a cavity space as small as 35mm for hassle-free installation.
- Dual control Flow and temperature are operated separately giving accurate control of both.
- Cartridge can be accessed from the front for easy servicing.
- 15mm inlet connections.
- Fitting depth including plasterboard and tiles is 60mm -75mm.
- 5-year parts and 1 year labour guarantee for peace of mind.
- Co-ordinating range of Bathroom taps available.

105 GI/2" (female) Ø250
15 215
50 348 80 40 105
GI/2" 80
GI/2" GI/2" 80

#### **Product Certifications:**



**♦** 8.6 l/min

Flow Rates (I/min)								
System Pressure (bar)	0.2	0.5	1	2	3	5		
Through Handset (mixed)	2.1	3.3	4.7	6.6	8.1	10.5		
Through Fixed Head (mixed)	2.2	3.5	5	7	8.6	11.1		
With Flow Limiters (mixed)	2	3.1	4.4	6.3	7.7	9.9		

## TECHNICAL DATA SHEET



BRISTAN