## FRM BF C

## FRAMMENTO Tap Range Frammento Bath Filler Chrome



Specification					
Product Type:	Bathroom Taps				
Main Construction Material:	Brass				
Mount Type:	Deck				
Handle Type:	Flat Angled				
Connection Inlet:	3/4" BSP				
Connection Outlet:	M24 Recessed Honeycomb Aerator				
Number of Tap Holes:	2				
Valve/Cartridge Type:	3/4" Short Stem Ceramic Disc Valve				
Plumbing System Requirements:	Suitable for all plumbing systems				
Minimum Dynamic Pressure (bar):	0.2 bar				
Maximum Dynamic Pressure (bar):	5 bar				
Maximum Hot Water Temperature °C:	60°C				
Maximum Static Pressure (bar):	10 bar				
Flow Type:	Single				
Isolation Included:	No				

Dimensions (measurements in mm)


## Features:


- Long life 1/4 turn ceramic disc valves for added durability and smooth control.
- Robust metal fixing nut to secure the tap in place reducing the risk of loosening over time.
- A hard-wearing, flawless, scratch resistant chrome finish that lasts for years. Salt spray tested to ensure added durability.
- 10-year parts and 1 year labour guarantee for peace of mind.
- Also available in black.
- Co-ordinating Bathroom taps available.

## **Product Certifications:**

For more products, visit our website: http://www.bristan.com







Flow Rates (I/min)								
System Pressure (bar)	0.2	0.5	1	2	3	5		
FRM BF C (mixed)	13.9	22.4	32.1	44.6	54.6	70.5		

TECHNICAL

