HYDROPOWER Power Shower Range

HY POWSHX W

Hydropower Thermostatic Power Shower White



$\Box \sim$	\rightarrow +			
ге	aι	ur	es:	

- Eco button for deactivation of pump
- 15mm push-fit inlet connections
- Thermostatic cartridge keeps water temperature within +/-1°C
- Push button start/stop with single temperature dial
- Includes hose, rub-clean antilimescale handset and riser rail
- Better Handset 3/Function white

Product Certifications:





For more products, visit our website: http://www.bristan.com



Specification					
Finish/Colour:	Matt Chrome/White				
Main Construction Material:	ABS Plastic				
No of Controls:	3				
Shower Type:	Power Shower 1500				
Shower Head Type:	Adjustable				
Working Pressure Range: (bar)	Min. 0.1 Bar, Max 1.0 Bar				
Maximum Static Pressure: (bar)	1				
Plumbing System Suitability:	Low Pressure Gravity Systems Only				
Connection Inlet:	15mm Push-Fit Inlet Connections				
Connection Outlet:	G 1/2" BSP				
Thermostatic:	Thermostatic				
Maximum Hot Water Supply Temperature	60				
Power Rating:	230v AC@50Hz/3Amp/150W				
Motor Rating:	15 mins. (unit will need to cool down if thermal cut out trips)				

Dimensions (measurements in mm)





Flow Rates (I/min)						
System Pressure (bar)	0.03	0.1	0.5			
Through Handset (Both Rings)	7.9	8.2	9.3			

TECHNICAL DATA SHEET



