IRIS Tap Range Iris Bath Filler Chrome





Features:

- A hard-wearing, flawless chrome finish that lasts for years
- Long life and easy to use 1/4 turn ceramic disc valves
- Supplied with metal fixing nuts to secure your tap in place
- Suitable for high and low pressure water systems
- 5 year guarantee

Product Certifications:



WRAS Cert, Number: 1909916 WRAS Expiry Date: 30/09/2024



For more products, visit our website: http://www.bristan.com

http://www.bristan.com							
	Flow Rates (I/min)						
	System Pressure (bar)	0.2	0.5	1	2	3	5
化输送机	IRS BF C (Mixed)	21.2	29.4	42	58	72	93
回該建設	IRS BF C (Hot)	13.5	22.1	31.4	44	54	70
	IRS BF C (Cold)	13.6	17.2	31.5	44.2	54.2	70.1





Bristan, Birch Coppice Business Park, Dordon, Tamworth, B78 1SG. Web Site: www.bristan.com Telephone: 0330 026 6273. Email: enquire@bristan.com.

* - Non-chrome product finishes carry a 3 year guarantee on finish. See www.bristan.com/guarantees for more information. The information contained on this page was correct at date of issue. Fitting Dimensions are provided as a guide only. Some variation may occur due to manufacturing tolerances. Bristan pursues a policy of continuous improvement in design and performance of its products and so reserves the right to change specifications without prior notice.

Specification					
Product Type:	Bathroom Taps				
Main Construction Material:	Brass				
Mount Type:	Deck Mounted				
Handle Type:	Lever Handles				
Connection Inlet:	3/4" BSP				
Connection Outlet:	M24 Aerator				
Number of Tap Holes:	2				
Valve/Cartridge Type:	3/4" Cermaic Disc Valves - 1/4 Turn				
Plumbing System Requirements:	Suitable for all plumbing systems				
Minimum Dynamic Pressure (bar):	0.2 bar				
Maximum Dynamic Pressure (bar):	5.0 bar				
Maximum Hot Water Temperature °C:	60°C				
Maximum Static Pressure (bar):	10 bar				
Flow Type:	Single Flow				
Isolation Included:	No				

Dimensions (measurements in mm)





BRISTA

D3

||4