# MIO BSM C

## MIOS Tap Range Mios Bath Shower Mixer Chrome Chrome



#### Features:

- Long life 1/4 turn ceramic disc valves for added durability and smooth control.
- Robust metal fixing nut to secure the tap in place reducing the risk of loosening over time.
- A hard-wearing, flawless, scratch resistant chrome finish that lasts for years. Salt spray tested to ensure added durability.
- Rub clean handset limescale and debris build-up is quickly and easily removed by rubbing a finger or a cloth over the nozzles. 5 year parts and 1 year labour guarantee for peace of mind.
- Co-ordinating Bathroom taps available.


#### **Product Certifications:**



\$

Specification				
Product Type:	Bathroom Taps			
Main Construction Material:	Brass			
Mount Type:	Deck Mounted			
Handle Type:	Lever Handles			
Connection Inlet:	G 3/4" BSP			
Connection Outlet:	Housed M24 Flow Straightener			
Number of Tap Holes:	2			
Valve/Cartridge Type:	Ceramic Disc Valves			
Plumbing System Requirements:	Suitable for all plumbing systems			
Minimum Dynamic Pressure (bar):	0.2 bar			
Maximum Dynamic Pressure (bar):	5.0 bar			
Maximum Hot Water Temperature °C:	60°C			
Maximum Static Pressure (bar):	10 bar			
Flow Type:	Single Flow			
Isolation Included:	No			

### Dimensions (measurements in mm)



D2

	Flow Rates (I/min)							
化输送机	System Pressure (bar)	0.2	0.5	1	2	3	5	
	Through Bath Filler (mixed)	13.1	21.6	30.9	44.1	53.1	68.6	
	Through Handset (mixed)	6.2	7.1	10.3	14.2	20.3	26.2	
TECHNICAL	ROUALA							
DATA	~~5							
	P YEARS 2							

Bristan, Birch Coppice Business Park, Dordon, Tamworth, B78 ISG. Web Site: www.bristan.com Telephone: 0330 026 6273. Email: enquire@bristan.com.

Non-chrome product finishes carry a 3 year guarantee on finish. See www.bristan.com/guarantees for more information. The information contained on this page was correct at date of issue. Fitting Dimensions are provided as a guide only. Some variation may occur due to manufacturing tolerances.

Fitting Dimensions are provided as a guide only. Some variation may occur due to manufacturing tolerances. Bristan pursues a policy of continuous improvement in design and performance of its products and so reserves the right to change specifications without prior notice.