NAPOLI Tap Range Napoli Bath Filler Chrome

NAP BF C



Features:

- Long life 1/4 turn ceramic disc • valves for added durability and smooth control.
- Robust metal fixing nut to secure the tap in place reducing the risk of loosening over time.
- A hard-wearing, flawless, scratch resistant chrome finish that lasts for years. Salt spray tested to ensure added durability.
- 10-year parts and 1 year labour guarantee for peace of mind.
- Co-ordinating Bathroom taps available.

Product Certifications:




WRAS Cert. Number: 2306906 WRAS Expiry Date: 30/06/2028

For more products, visit our website: http://www.bristan.com

Specification				
Product Type:	Bathroom Taps			
Main Construction Material:	Brass			
Mount Type:	Deck			
Handle Type:	Lever			
Connection Inlet:	3/4" BSP			
Connection Outlet:	M24 Recessed Aerator			
Number of Tap Holes:	2			
Valve/Cartridge Type:	3/4" Ceramic Disc Valve			
Plumbing System Requirements:	Suitable for all plumbing systems			
Minimum Dynamic Pressure (bar):	0.2 bar			
Maximum Dynamic Pressure (bar):	5 bar			
Maximum Hot Water Temperature °C:	60°C			
Maximum Static Pressure (bar):	10 bar			
Flow Type:	Single			
Isolation Included:	No			

Dimensions (measurements in mm)



高粱	Flow Rates (I/min)							
	System Pressure (bar)	0.2	0.5	1	2	3	5	
	NAP BF C (mixed)	14.2	23.4	34.5	48.6	59.5	76.8	
TECHNICAL DATA SHEET	or QUACIA Soverars 2 Aran Tel Paran Tel +		B	RIS	ST/		D4	

Bristan, Birch Coppice Business Park, Dordon, Tamworth, B78 ISG. Web Site: www.bristan.com Telephone: 0330 026 6273. Email: enquire@bristan.com.

* - 10 year guarantee applies to products purchased on or after 01/04/2021. Non-chrome product finishes carry a 3 year guarantee on finish. See www.bristan.com/guarantees for more information. The information contained on this page was correct at date of issue. Fitting Dimensions are provided as a guide only. Some variation may occur due to manufacturing tolerances. Bristan pursues a policy of continuous improvement in design and performance of its products and so reserves the right to change specifications without prior notice.