RU SNK EF C

RUBY Tap Range Ruby Easyfit Mono Sink Mixer Chrome



_							s:
_	$^{\circ}$	\mathbf{a}	т	11	\boldsymbol{r}	\frown	С.
	ᆫ	a	u	u		C	Э.

- Long life ceramic cartridge for added durability and ease of
- Metal fixing nut for added durability

Easyfit base included Flexible tails included

Product Certifications:

WRAS

WRAS Certificate No: 2201900 WRAS Expirty Date: 31/01/2027




♦24.2 l/min

For more products, visit our website: http://www.bristan.com



Specification						
Product Type:	Kitchen Taps					
Main Construction Material:	Brass					
Mount Type:	Deck Mounted					
Handle Type:	Lever Handle					
Connection Inlet:	1/2" BSP Flexible Tails					
Connection Outlet:	M24 Flow Straightener					
Number of Tap Holes:	1					
Valve/Cartridge Type:	Ceramic Cartridge					
Plumbing System Requirements:	Suitable for all plumbing systems					
Minimum Dynamic Pressure (bar):	0.3 bar					
Maximum Dynamic Pressure (bar):	5.0 bar					
Maximum Hot Water Temperature °C:	65°C					
Maximum Static Pressure (bar):	10 bar					
Flow Type:	Single Flow					
Isolation Included:	Yes					

Dimensions (measurements in mm)



Flow Rates (I/min)										
System Pressure (bar)	0.3	0.5	1	2	3	5				
RU SNK EF C (mixed)	7.6	9.8	13.9	19.7	24.2	31				

TECHNICAL



