Mira Relate ERD

Mixer Shower





A sleek, modern combination of a spa-like deluge and separate practical handshower, providing a consistently genuine performance.

Product Information

Description	Colour	Product No.
Mira Relate ERD	Chrome	2.1878.002

Features & Benefits

reatures & benefits	
Temperature control	
Thermostatic temperature stability	
Easy to fit	
Front of tile installation system	
Easy to service	
Large, long-life filters and replaceable cartridge	
For your customer	
Separate flow and temperature controls	
Maximum temperature stop for increased safety (with override for a hotter shower)	
Mira Cool Shield $^{\text{TM}}$ to ensure valve doesn't get hot during showering	
Mira Magni-flo™ technology delivers up to 3x more flow, even at low pressure	
1 spray 9cm showerhead with rub-clean nozzles	
Large 200mm deluge showerhead	





Technical Details

Temperature contro

Control type: Thermostatic

Installation

Water entry points: rear only (bar valve exposed pipework installation elbows available for rising or falling inlets)

Inlet connections: 1/2" BSP to pipework, 3/4" BSP to shower unit

Outlet connections: $\frac{1}{2}$ " BSP Male

Adjustable pipe centres: 150mm ± 24mm

Reversed inlets supported: No = hot left, cold right only

Supply Conditions (hot and cold)

Cold water range: Up to 25°C Hot water range: 60°C - 65°C

Minimum maintained pressure: 0.1 bar (1 metre head)

Maximum maintained pressure: 5.0 bar (50 metre head)

Maximum static pressure: 10.0 bar (100 metre head)

erformance

Flow rate (at handset): 10.2 l/min at 0.5 bar

Temperature stability: ± 2°C

Safety Features

Automatic shutdown: Shutdown within 2 secs

Factory set to safe max temp: Factory set to 41°C

Adjustable maximum temperature for on-site conditions

Approval

KIWA UK approved product

WRAS approved (Water Regulations Advisory Scheme)





Dimensions



