

Technical Data Sheet

Craft Shower Systems

ROPER RHODES®

| No. | Description | Code | Fixings Included |
|-----|--|----------|------------------|
| 1 | Craft Dual Function Shower System With Fixed Head & Riser Rail | SVSET149 | YES |



| Inlet Pressure | Flow Rate (l/min) |
|----------------|-------------------|
| 0.5bar | 15.91 |
| 1bar | 22.50 |
| 2bar | 31.82 |
| 3bar | 35.00 |
| 4bar | 45.00 |
| 5bar | 49.86 |

Flow from valve may vary depending on accessories and domestic supply.

Components - SVSET149

Diagrams not to scale. All dimensions in mm (tolerance of +/-5mm)

- Dual Function Thermostatic Shower Valve - SV3506
- 460mm Adjustable Brass Fixed Arm - SVARM01
- 250mm Stainless Steel Shower Head - SVHEAD12
- Air-drive Five Function Shower Handset - SVHEAD29
- Brass Shower Hose - SVHOSE01
- Riser Rail - SVRAIL05
- Outlet Elbow With Shower Handset Holder - SVACS03

FAQs

What is the rail fixing centres? 595mm

How long is the shower hose? 1.5m

What is the minimum pressure for the valve? 0.3bar

What is the valve connection size? 1/2"