



great value from...

AQUALISA

Shower system packs

Fantastic value high performance showers

- Concealed and surface mounted thermostatic shower systems available
- Proven, reliable thermostatic technology
- Shower valves suitable for use with all approved domestic plumbing systems
- Integral anti-scale mechanism
- Supplied complete with adjustable height shower kit
- High flow multi mode handset complete with rub clean nozzles
- 2 year parts and labour guarantee



concealed and surface mounted valves available

609.BIV.01 concealed flexi shower system in chrome

99.EV.01 surface mounted flexi shower system in chrome

Technical information

609.BIV.01

Concealed flexi shower system in chrome

CONCEALED SYSTEM

Thermostatic concealed valve ergonomically styled

FIXING DATA

INLETS

15mm push-fit swivel elbow connectors.

150mm pipe centres.

Hot left/cold right viewed from front.

ACCESSORIES

213039 Easy grip knob

TYPICAL GRAVITY FLOW RATE

8lpm at 1m head (via shower head)

WATER PRESSURES

Minimum: 0.1 bar (1 metre head).

Maximum: 10 bar (100 metre head).

WATER SYSTEM COMPATIBILITY

Gravity Combi Mains fed Unvented



99.EV.01

Surface mounted flexi shower system in chrome

SURFACE MOUNTED SYSTEM

Thermostatic surface mounted valve for quick and easy installation

FIXING DATA

INLETS

15mm push-fit connectors.

150mm centres.

Pipe projection for rear entry – 18-22mm.

Hot left/cold right viewed from front.

ACCESSORIES

E99MF.01 Manifold adapter to accept top or bottom entry pipework

TYPICAL GRAVITY FLOW RATE

8lpm at 1m head (via shower head)

WATER PRESSURES

Minimum: 0.1 bar (1 metre head).

Maximum: 10 bar (100 metre head).

WATER SYSTEM COMPATIBILITY

Gravity Combi Mains fed Unvented



AQUALISA
www.aqualisa.co.uk

PART NO 166120 Q2566_ISSUE 01 AUG09

Sales enquiries and orders
01959 560010