# Mira Advance ATL Flex Low Pressure

**Electric Shower** 

Ultimate in safety, and endorsed by the Royal National Institute of the Blind. Featuring an integral pump for best in class performance at low pressure.

# **Product Information**

Description	Colour	Product No.
Mira Advance ATL Flex Low Pressure 9.0kW	White/Chrome	1.1759.003

# Features & Benefits

Temperature control		
Thermostatic temperature stability		
Easy to service		
Easy filter access		
For your customer		
Separate flow and temperature controls.		
Push button on/off		
8 different maximum temperature settings		
Phased shutdown flushes hot water from the tank making it safe for the next user		
Rotary lever with large loop and audible click		
Tactile raised areas, large backlit buttons and an audible beep to aid navigation		
Easy to use slide bar and friction bracket which can be adjusted with one hand		
Best in class for reducing limescale		
Best in class for performance at low pressure		
4 spray 11cm showerhead with rub-clean nozzles		





## **Tech Details**

Control type: Thermostatic (electronic)

Power options: 9.0kW 240V AC (8.2kW 230V AC)

Supply voltage:  $230v \pm 10\%$ Supply rating: 40 amp (9.0kW)

Terminal Block connections: Maximum 16mm2

Water entry points: Right (rising, falling or rear)

Cable entry points: Right (rising, falling or rear) Inlet connections: Brass inlet connector.  $\,1\!\!/2''$  BSP Male and 15mm

compression fitting

Outlet connections: 1/2" BSP Male

Minimum maintained pressure: 0.008 bar (80 mm head)

Maximum maintained pressure: 1.0 bar (10 metre head)

Maximum static pressure: 1.0 bar (10 metre head)

Temperature stability:  $\pm 1$ °C

Phased shutdown: Yes

Factory set to safe max temp: Adjustable to 8 different max temp

settings (37°C - 48°C)

### **IMPORTANT:**

This is a pumped electric shower for installation onto gravity fed cold water cisterns. It is not suitable for installation directly onto cold mains supplies.

## **Dimensions**







