Mira Miniluxe ER

SUITABLE FOR ALL SYSTEMS



Mixer Shower

Make a statement in your bathroom. The luxurious deluge showerhead delivers greater coverage and a greater experience.



Description	Colour	Product No.
Mira Miniluxe ER	Chrome	1.1660.007

Features & Benefits

Temperature control

Thermostatic temperature control and maximum temperature stop

Easy to fit

Front of tile installation system

Easy to service

Large, long-life filters

For your customer

Separate flow and temperature controls

Mira Magni-flo™ technology delivers up to 3x more flow, even at low pressure

Cool Shield™ technology ensures the valve

doesn't get hot during showering

Large 18.5cm deluge head with rub-clean nozzles

for greater showering experience

Works on all systems, even at low pressure







Tech Details

Temperature control

Control type: Thermostatic

Installation

Water entry points: Rear only

Inlet connections: 15mm compression

Outlet connections: 15mm compression

Reversed inlets supported: No = hot top, cold bottom only

Supply Conditions (hot and cold)

Cold water range: Up to 25°C

Hot water range: 60°C-65°C

Minimum maintained pressure: 0.1 bar (1 metre head)

Maximum maintained pressure: 5.0 bar (50 metre head)

Maximum static pressure: 10.0 bar (100 metre head)

Performance

Flow rate (at showerhead): 14 l/min at 0.5 bar

Temperature stability: ± 2°C

Safety Features

Automatic shutdown: Shutdown within 2 secs

Factory set to safe max temp: Factory set to 43°C

Adjustable maximum temperature for on-site conditions

Approvals

WRAS approved (Water Regulations Advisory Scheme)

KIWA UK Approved



Dimensions



