K BSM C

COLONIAL Tap Range

Colonial Bath Shower
Mixer Chrome



| Specification | | | | |
|-----------------------------------|------------------------------------|--|--|--|
| Product Type: | Bathroom Taps | | | |
| Main Construction Material: | Brass | | | |
| Mount Type: | Deck | | | |
| Handle Type: | Crosshead | | | |
| Connection Inlet: | 3/4" BSP | | | |
| Connection Outlet: | G 1/2" | | | |
| Number of Tap Holes: | 2 | | | |
| Valve/Cartridge Type: | 1/2" Ceramic Disc Valve - 1/4 turn | | | |
| Plumbing System Requirements: | Suitable for all plumbing systems | | | |
| Minimum Dynamic Pressure (bar): | 0.2 bar | | | |
| Maximum Dynamic Pressure (bar): | 5 bar | | | |
| Maximum Hot Water Temperature °C: | 65°C | | | |
| Maximum Static Pressure (bar): | 10 bar | | | |
| Flow Type: | Single | | | |
| Isolation Included: | No | | | |

Dimensions (measurements in mm)

Features:

- Rub clean handset limescale and debris build-up is quickly and easily removed by rubbing a finger or a cloth over the nozzles.
- Robust metal fixing nut to secure the tap in place reducing the risk of loosening over time.
- A hard-wearing, flawless, scratch resistant chrome finish that lasts for years. Salt spray tested to ensure added durability.
- 10 year parts and 1 year labour guarantee for peace of mind.
- Co-ordinating Bathroom taps and Accessories available

Product Certifications:



WRAS Certificate No: 2209053 WRAS Expiry Date: 30/09/2027



215 260 180 180 160 235

| Flow Rates (I/min) | | | | | | | | |
|-----------------------------|------|-----|------|------|------|------|--|--|
| System Pressure (bar) | 0.2 | 0.5 | 1 | 2 | 3 | 5 | | |
| Through Bath Filler (mixed) | 10.7 | 19 | 27.3 | 37.6 | 53.5 | 65.2 | | |
| Through Handset (mixed) | 5 | 8.1 | 11.8 | 17.2 | 21.2 | 29.4 | | |

TECHNICAL DATA SHEET



